



cavi zenit



CAVI ZENIT SRL Via Ganna 27, 21039 Bedero Valcuvia (VA) TEL. 0332/724512- FAX 0332/725145

E-mail: info@cavizenit.it- www.cavizenit.it C.F. Iscr. Reg. Impr. Varese 02143560122

Trib. Di Varese 20379- Cap. Soc. € 10400,00 i.v. Partita IVA IT 02143560122

Descrizione Cavo / description: Cavo unipolare in rame rosso elettrolitico CU ETP1 / unipolar cable red electrolytic copper CU ETP1

Temperatura d'esercizio / use temperature: -50°C / + 150°C

Documenti di Riferimento / reference documents: ISO 6722 CLASSE D - FLR13Y- CEI EN 60228 - UL 94V2 - LV112

Colori / colours: a richiesta / by request

caratteristiche tecniche / technical characteristics								
codice/code	sezione-cross section	formaz. Cond. / cond. Constr.	passo tref.-lay lenght	D.est -ext. Diametr.	materiale isol. / insul. Material	Res. El. Max 20° / El. Res. Max 20°	Tens. esercizio / Max volt.	Corrente Max / Max El. current
11035T0000F125S1	1x0,35	7x0,25±0,01 mm	< 40 mm	1,25±0,05 mm	TPC-ES T4 HT 150°C	52,0 Ohm/km	<300 V	3,2 A
11050T0000F155S1	1x0,50	16x0,20±0,01 mm	<50 mm	1,50±0,10 mm	TPC-ES T4 HT 150°C	37,1 Ohm/km	<300 V	6,0 A
11075T0000F185S1	1x0,75	24x0,20±0,01 mm	<60 mm	1,80±0,10 mm	TPC-ES T4 HT 150°C	24,7 Ohm/km	<300 V	9,0 A
11100T0000F210S1	1x1,00	32x0,20±0,01 mm	<70 mm	1,95±0,10 mm	TPC-ES T4 HT 150°C	18,5 Ohm/km	<300 V	11,0 A
11150T0000F235S1	1x1,50	30x0,25±0,01 mm	<70 mm	2,25±0,10 mm	TPC-ES T4 HT 150°C	12,7 Ohm/km	<300 V	14,0 A
11200T0000F290S1	1x2,00	40x0,25±0,01 mm	<85 mm	2,55±0,10 mm	TPC-ES T4 HT 150°C	9,42 Ohm/km	<300 V	16,0 A
11250T0000F290S1	1x2,50	50x0,25±0,01 mm	<85 mm	2,80±0,10 mm	TPC-ES T4 HT 150°C	7,6 Ohm/km	<300 V	20,0 A
11400T0000F360S1	1x4,00	56x0,30±0,01 mm	< 85 mm	3,50±0,10 mm	TPC-ES T4 HT 150°C	4,7 Ohm/km	<300 V	28,0 A
11600T0000F425S1	1x6,00	84x0,30±0,01 mm	< 85 mm	4,20±0,10 mm	TPC-ES T4 HT 150°C	3,1 Ohm/km	<300 V	37,0 A
11110T0000F550S1	1x10,00	78x0,40±0,01 mm	< 100mm	5,50±0,20 mm	TPC-ES T4 HT 150°C	1,82 Ohm/km	<300 V	48,0 A
11116T0000F750S1	1x16,00	7x18x0,40±0,01 mm	<100 mm	7,30±0,20 mm	TPC-ES T4 HT 150°C	1,16 Ohm/km	<300 V	75,0 A

Rev.N°: 1

Preparato e verificato da / prepared and verified by : **Maurizio Galli, Quality Manager**

Data / Date 04/03/2011

PAG: 1/1